

## GOM-801H Specifications

The specifications apply when the GOM-801H is powered on for at least 30 minutes under +18°C~+28°C.



<b>TEST RANGE</b>	
	20, 200mΩ, 2, 20, 200Ω, 2k, 20kΩ 7 Ranges
<b>TEST CURRENT (Test Voltage 0.2V)</b>	
	20mΩ/200mΩ: 1A 2Ω: 0.1A 200Ω: 1mA 2kΩ: 100uA 20kΩ: 10uA
<b>ACCURACY</b>	
Measurement	20mΩ: ± (0.2% rdg + 6 digits) 200mΩ ~ 20kΩ: ± (0.2% rdg + 4 digits)
Setting	± (0.2% + 6 digits)
<b>RESOLUTION</b>	
	0.01Ω, 0.1Ω, 1Ω, 10Ω, 100mΩ, 1Ω, 10Ω
<b>COMPARATOR</b>	
	HI, LO settable
<b>DISPLAY</b>	
	3 1/2 digits 0.5" LED display HI, GO, LO indicator
<b>POWER SOURCE</b>	
	AC 100V/120V/220V/230V±10%, 50/60Hz; Power consumption: 25VA max.
<b>DIMENSIONS &amp; WEIGHT</b>	
	230(W) x 95(H) x 280(D)mm; Approx. 2 kg