

ASR-6000 Series Parallel Models Specifications

SPECIFICATIONS		
Model		ASR-6600-24
Input Ratings		
Power type	Three-phase Three-wire Delta connection Three-phase Four-wire Y connection	
Voltage range ¹	200 Vac to 240 Vac (Phase Voltage) 380 Vac to 460 Vac (Line Voltage)	
Frequency range	47 Hz to 63 Hz	
Power factor ²	0.95 or higher (typ.)	
Efficiency ²	80 % or higher	
Maximum power consumption	32 kVA or lower	
AC Output		
Multi-phase output	Single-phase output	Polyphase output
Output capacity	24 kVA	1P3W: 18 kVA 3P4W: 24 kVA
Mode	1P2W	1P3W 3P4W (Y-connection)
Setting mode ³	---	Unbalance, Balanced
Phase voltage	Setting Range ⁴	0.00 V to 175.0 V / 0.0 V to 350.0 V (sine and square wave), Setting Resolution: 0.01 V / 0.1 V
	Accuracy ⁵	±(0.3 % of set + 0.5 V / 1 V)
Line voltage setting range ⁶	---	1P3W: 0.00 V to 350.0 V / 0.0 V to 700.0 V 3P4W: 0.00 V to 303.1 V / 0.00 V to 606.2 V (sine wave only) Setting Resolution: 0.01 V / 0.1 V
Maximum current ⁷	240 A / 120 A	80 A / 40 A
Maximum peak current ⁸	Four times of the maximum RMS current	
Load power factor ⁹	0 to 1 (leading phase or lagging phase, 45 Hz to 65Hz)	
Frequency	Setting range	AC Mode: 15.00 Hz to 550.0 Hz, AC+DC Mode: 1.00 Hz to 550.0 Hz, Setting resolution: 0.01 Hz / 0.1 Hz
	Accuracy	± 0.01% of set
	Stability ¹⁰	± 0.005%
Output on phase setting range ¹¹	0.0° to 359.9° variable (Free / Fix selectable), 0.1° (1 Hz to 500 Hz), 1° (500 Hz to 550 Hz)	
Output off phase setting range ¹¹	0.0° to 359.9° variable (Free / Fix selectable), 0.1° (1 Hz to 500 Hz), 1° (500 Hz to 550 Hz)	
Setting range of the phase angle ¹²	---	3P4W: L2 phase: 0° to 359.9° L3 phase: 0° to 359.9° Setting Resolution: 0.1°
Phase angle accuracy ¹³	---	45 Hz to 65 Hz: ±1.0° 15 Hz to 550 Hz: ±2.0°
DC offset ¹⁴	± 20 mV (typ.)	
DC output (only single phase output)		
Output Capacity		24 kW
Mode	Floating output, the N terminal can be grounded	
Voltage	Setting Range	-250.0 V to +250.0 V / -500.0 V to +500.0 V, Setting Resolution: 0.01 V / 0.1 V
	Accuracy ¹⁵	±[(0.3 % of set) + 0.3 V / 0.6 V]
Maximum current ¹⁶	240 A / 120 A	
Maximum peak current ¹⁷	Four times of the maximum current	
Output Stability, Total Harmonic Distortion, Output voltage rising time and Ripple noise		
Line regulation	±0.1% or less (Phase voltage)	
Load regulation ¹⁸	±1 V / ±2 V (phase voltage, 0 to 100%, via output terminal)	
Distortion of Output ¹⁹	<0.3 % @1Hz to 100Hz, <0.5 % @ 100.1 Hz to 550 Hz	
Output voltage response time ²⁰	Medium: 100 μs (typ.) ; Slow: 300 μs (typ.)	
Ripple noise ²¹	0.5 Vrms / 1 Vrms (TYP)	
<p>¹ Y connection is three-phase, five-wire, Delta connection is three-phase, four-wire.</p> <p>² In the case of AC-INT mode, the rate output voltage, resistance load at maximum output current, 45 Hz to 65 Hz and sine wave output only.</p> <p>³ Can be only set in 3P4W mode.</p> <p>⁴ For phase voltage setting in polyphase output. In balance mode all phase are collectively set and in unbalance mode each phases are individually set.</p> <p>⁵ For an output voltage of 10 V to 175 V / 20 V to 350 V, sine wave, an output frequency of 45 Hz to 65 Hz, no load, DC voltage setting 0V (AC+DC mode) and 23°C ± 5°C. For phase voltage setting in the polyphase output.</p> <p>⁶ Line voltage only can be set in balance mode.</p> <p>⁷ If the output voltage is higher than rated value, this is limited to satisfy the power capacity. If there is the DC superimposition, the active current of AC+DC satisfies the maximum current. In the case of 40 Hz or lower or 400 Hz or higher, and that the ambient temperature is 40 degree or higher, the maximum current may decrease.</p> <p>⁸ With respect to the capacitor-input rectifying load. Limited by the maximum current.</p> <p>⁹ External power injection or regeneration which is over short reverse power flow capacity is not available.</p> <p>¹⁰ For 45 Hz to 65 Hz, the rated output voltage, no load and the resistance load for the maximum current, and the operating temperature range.</p> <p>¹¹ L1, L2 and L3 phase can be set independ at independ mode in the polyphase output.</p> <p>¹² Can be set only with independ mode in polyphase output.</p> <p>¹³ For an output voltage of 50V or higher, sine wave, same load and voltage condition for all phase.</p> <p>¹⁴ In the case of the AC mode and output voltage setting to 0 V, 23°C ± 5°C</p> <p>¹⁵ For an output voltage of -250 V to -10 V, +10 V to +250 V / -500 V to -20 V, +20 V to +500 V, no load, AC voltage set to 0V (AC+DC mode) and 23°C ± 5°C</p> <p>¹⁶ If the output voltage is higher than rated value, this is limited to satisfy the power capacity. If there is the AC superimposition, the active current of AC+DC satisfies the maximum current. And the ambient temperature is 40 degree or higher, the maximum current may decrease.</p> <p>¹⁷ Instantaneous within 3 ms, limited by the maximum current at rated output voltage.</p> <p>¹⁸ For an output voltage of 75 V to 175 V / 150 V to 350 V, a load power factor of 1, stepwise change from an output current of 0 A to maximum current (or its reverse), using the output terminal on the rear panel.</p> <p>¹⁹ 50 % or higher of the rated output voltage, the maximum current or lower, AC and AC+DC modes, THD+N. For the polyphase output, it is a specification for phase voltage setting.</p> <p>²⁰ For an output voltage of 100 V / 200 V, a load power factor of 1, with respect to stepwise change from an output current of 0 A to the maximum current (or its reverse). 10% - 90% of output voltage.</p> <p>²¹ For 5 Hz to 1 MHz components in DC mode using the output terminal on the rear panel.</p>		

Measured value display (All accuracy of the measurement function is indicated for 23 °C±5 °C.)			
		Single-phase output	Polyphase output ^{*6}
Voltage ^{*1,2}	Resolution	0.01 V / 0.1 V	
	RMS value accuracy	45 Hz to 65 Hz and DC: ±(0.5% of rdg + 0.5 V / 1 V) 15 Hz to 550 Hz: ±(0.7% of rdg + 1 V / 2 V)	45 Hz to 65 Hz: ±(0.5% of rdg + 0.5 V / 1 V) 15 Hz to 550 Hz: ±(0.7% of rdg + 1 V / 2 V)
	AVG value accuracy	DC: ±(0.5% of rdg) + 0.5 V / 1 V	DC: ±(0.5% of rdg) + 0.5 V / 1 V
	PEAK value accuracy ^{*3}	45 Hz to 65 Hz and DC: ±(2% of rdg) + 1 V / 2 V	45 Hz to 65 Hz: ±(2% of rdg) + 1 V / 2 V
Current ^{*4}	Resolution	0.01 A / 0.1 A	
	RMS value accuracy	45 Hz to 65 Hz and DC: ±(0.5% of rdg + 0.3 A / 0.15 A) 15 Hz to 550 Hz: ±(0.7% of rdg + 0.6 A / 0.4 A)	45 Hz to 65 Hz: ±(0.5% of rdg + 0.15 A / 0.08 A) 15 Hz to 550 Hz: ±(0.7% of rdg + 0.3 A / 0.15 A)
	AVG value accuracy	DC: ±(0.5% of rdg) + 0.6 A / 0.4 A	DC: ±(0.5% of rdg) + 0.3 A / 0.15 A
	PEAK value accuracy ^{*5}	45 Hz to 65 Hz and DC: ±(2% of rdg) + 3 A / 1.5 A	45 Hz to 65 Hz: ±(2% of rdg) + 1.5 A / 0.75 A
Power ^{*7,8}	Active (W)	Resolution	0.1 W / 1 W / 10 W
		Accuracy ^{*9}	±(2% of rdg + 9 W)
	Apparent (VA)	Resolution	0.1 VA / 1 VA / 10VA
		Accuracy	±(2% of rdg + 18 VA)
	Reactive (VAR)	Resolution	0.1 VAR / 1 VAR / 10VAR
		Accuracy ^{*10}	±(2% of rdg + 18 VAR)
Power factor	Range	0.000 to 1.000	
Harmonic voltage Effective value (rms) Percent (%) (AC-INT and 50/60 Hz only) ^{*11}	Resolution	0.001	
	Range	Up to 100th order of the fundamental wave	
	Full Scale	200 V / 400 V, 100%	
	Accuracy ^{*12}	Up to 20th: ±(0.2% of rdg + 0.5 V / 1 V) 21th to 100th: ±(0.3% of rdg + 0.5 V / 1 V)	
Harmonic current Effective value (rms) Percent (%) (AC-INT and 50/60 Hz only) ^{*11}	Resolution	0.01 A / 0.1 A / 1 A, 0.1%	84 A / 42 A, 100%
	Range	Up to 100th order of the fundamental wave	
	Full Scale	252 A / 126 A, 100%	
	Accuracy ^{*13}	Up to 20th: ±(1% of rdg + 3 A / 1.5 A) 21th to 100th: ±(1.5% of rdg + 3 A / 1.5 A)	Up to 20th: ±(1% of rdg + 1 A / 0.5 A) 21th to 100th: ±(1.5% of rdg + 1 A / 0.5 A)

*1. In the polyphase output, the specification is for phase voltage, and the DC average value display cannot be selected.
*2. Accuracy values are in the case that the output voltage is within voltage setting range.
*3. The accuracy is for output waveform DC or sine wave only.
*4. Accuracy values are in the case that the output current is 5% to 100% of the maximum current.
*5. The accuracy is for output waveform DC or sine wave only.
*6. In the polyphase output, these are the specifications for each phase.
*7. For an output voltage of 50 V or greater, an output current in the range of 10% to 100% of the maximum current, DC or an output frequency of 45 Hz to 65 Hz.
*8. The apparent and reactive powers are not displayed in the DC mode.
*9. For the load with the power factor 0.5 or higher.
*10. For the load with the power factor 0.5 or lower.
*11. The measurement does not conform to the IEC or other standard. Phase Voltage and Phase Current.
*12. For an output voltage of 10 V to 175 V / 20 V to 350 V.
*13. An output current in the range of 5% to 100% of the maximum current.

Others			
Protections		UVP, OVP, OCP, OTP, OPP, Fan Fail, Peak and RMS Current Limit	
Display		TFT-LCD, 7 inch	
Memory function		Store and recall settings, Basic settings: 10	
Arbitrary Wave	Number of memories	253 (nonvolatile)	
	Waveform length	4096 words	
	Amplitude resolution	16 bits	

General Specifications			
Interface	Standard	USB	Type A: Host, Type B: Slave, Speed: 2.0, USB-CDC / USB-TMC
		LAN	MAC Address, DNS IP Address, User Password, Gateway IP Address, Instrument IP Address, Subnet Mask
		External	External Signal Input External Control I/O V/I Monitor Output
		RS-232C	Complies with the EIA-RS-232 specifications
	Optional 1	GPIO	SCPI-1993, IEEE 488.2 compliant interface
	Optional 2	CAN Bus	Complies with CAN 2.0A or 2.0B based protocol
Optional 3	Device Net	Complies with CAN 2.0A or 2.0B based protocol	
Insulation resistance	Between input and chassis, input and output	DC 500 V, 30 MΩ or more	
Withstand voltage	Between input and chassis, input and output	AC 1500 V or DC 2130 V, 1 minute	
EMC		EN 61326-1 (Class A) EN 61326-2-1/2-2 (Class A) EN 61000-3-2 (Class A, Group 1) EN 61000-3-3 (Class A, Group 1) EN 61000-4-2/-4-3/-4-4/-4-5/-4-6/-4-8/-4-11 (Class A, Group 1) EN 55011 (Class A, Group1)	
Safety		EN 61010-1	
Environment	Operating environment	Indoor use, Overvoltage Category II	
	Operating temperature range	0 °C to 40 °C	
	Storage temperature range	-10 °C to 70 °C	
	Operating humidity range	20 %rh to 80 % RH (no condensation)	
	Storage humidity range	90 % RH or less (no condensation)	
	Altitude	Up to 2000 m	
Dimensions (mm) (not including protrusions)		598(W)×1294(H)×906(D)	
Weight		Approx. 250 kg	

A value with the accuracy is the guaranteed value of the specification. However, an accuracy noted as reference value shows the supplemental data for reference when the product is used, and is not under the guarantee. A value without the accuracy is the nominal value or representative value (shown as typ.).
Product specifications are subject to change without notice.