

**GDM-9061 規格**

規格適用於 GDM-9061 規格在環境中熱機至少 60 分鐘時



(with optional GPIB)

**Note :**

- All specifications are ensured only under a single display.
- At least 1 hour of warm-up time is required before applying these specifications.
- Make sure that the Sense LO terminal to Input LO is limited to 2 Vpk, the Sense HI to Sense LO terminals are limited to 200 Vpk and the Input LO to earth is limited to 500 Vpk. CAT II 300 V. MAX DC 1000 V, AC 750 V

功能	檔位(2)	解析度	輸入電阻 其他	24 小時 TCAL ± 1 °C	90 天 TCAL ± 5 °C	1 年 TCAL ± 5 °C	溫度係數 0 °C to 18 °C / 28 °C to 55 °C
<b>直流特性</b> Accuracy : ± (% of reading + % of range)							
直流電壓 (1)	100.0000 mV	0.1 μV	10 MΩ or > 10 GΩ	0.0030 + 0.0030	0.0040 + 0.0035	0.0050 + 0.0035	0.0005 + 0.0005
	1.000000 V	1 μV	10 MΩ or > 10 GΩ	0.0020 + 0.0006	0.0035 + 0.0007	0.0048 + 0.0007	0.0005 + 0.0001
	10.00000 V	10 μV	10 MΩ or > 10 GΩ	0.0015 + 0.0004	0.0020 + 0.0005	0.0035 + 0.0005	0.0005 + 0.0001
	100.0000 V	0.1 mV	10 MΩ ± 1%	0.0020 + 0.0006	0.0035 + 0.0006	0.0050 + 0.0006	0.0005 + 0.0001
	1000.000 V	1 mV	10 MΩ ± 1%	0.0025 + 0.0006	0.0040 + 0.0010	0.0050 + 0.0010	0.0005 + 0.0001
電阻 (1)(3)	100.0000 Ω	100 μΩ	1 mA	0.003 + 0.0030	0.008 + 0.004	0.010 + 0.004	0.0008 + 0.0005
	1.000000 kΩ	1 mΩ	1 mA	0.002 + 0.0005	0.008 + 0.001	0.010 + 0.001	0.0008 + 0.0001
	10.00000 kΩ	10 mΩ	100 μA	0.002 + 0.0005	0.008 + 0.001	0.010 + 0.001	0.0008 + 0.0001
	100.0000 kΩ	100 mΩ	10 μA	0.002 + 0.0005	0.008 + 0.001	0.010 + 0.001	0.0008 + 0.0001
	1.000000 MΩ	1 Ω	5 μA	0.002 + 0.0010	0.008 + 0.001	0.010 + 0.001	0.0010 + 0.0002
	10.00000 MΩ	10 Ω	500 nA	0.015 + 0.0010	0.020 + 0.001	0.040 + 0.001	0.0030 + 0.0004
	100.0000 MΩ	100 Ω	500 nA// 10 MΩ	0.300 + 0.0100	0.800 + 0.010	0.800 + 0.010	0.1500 + 0.0002
直流電流 (1)(6)	100.0000 μA	100 pA	< 0.11 V	0.010 + 0.020	0.040 + 0.025	0.050 + 0.025	0.002 + 0.003
	1.000000 mA	1 nA	< 0.11 V	0.007 + 0.006	0.030 + 0.006	0.050 + 0.006	0.002 + 0.001
	10.00000 mA	10 nA	< 0.04 V	0.007 + 0.020	0.030 + 0.020	0.050 + 0.020	0.002 + 0.002
	100.0000 mA	100 nA	< 0.4 V	0.010 + 0.004	0.030 + 0.005	0.050 + 0.005	0.002 + 0.001
	1.000000 A	1 μA	< 0.7 V	0.050 + 0.006	0.080 + 0.010	0.100 + 0.010	0.005 + 0.001
	3.000000 A	1 μA	< 2.0 V	0.180 + 0.020	0.200 + 0.020	0.200 + 0.020	0.005 + 0.002
	10.00000 A	10 μA	< 0.5 V	0.100 + 0.010	0.120 + 0.010	0.150 + 0.010	0.005 + 0.001
短路峰鳴 (1)	1000.000 Ω	0.001 Ω	1 mA	0.002 + 0.030	0.008 + 0.030	0.01 + 0.030	0.001 + 0.002
二極體 (1)(4)	5.00000 V	10 μV	1 mA	0.002 + 0.030	0.008 + 0.030	0.01 + 0.030	0.001 + 0.002
DC Ratio (1)(5)	—	—	—	± (DC Input accuracy + DC Reference accuracy)			

交流特性		Accuracy : ± (% of reading + % of range)					
True RMS 交流電壓 (7)(8)(9)(10)	100.0000 mV	0.1 μV	3 Hz to 5 Hz	1.00 + 0.03	1.00 + 0.04	1.00 + 0.04	0.100 + 0.004
			5 Hz to 10 Hz	0.35 + 0.03	0.35 + 0.04	0.35 + 0.04	0.035 + 0.004
			10 Hz to 20 kHz	0.04 + 0.03	0.05 + 0.04	0.06 + 0.04	0.005 + 0.003
			20 kHz to 50 kHz	0.10 + 0.05	0.11 + 0.05	0.12 + 0.05	0.011 + 0.005
			50 kHz to 100 kHz	0.55 + 0.08	0.60 + 0.08	0.60 + 0.08	0.060 + 0.008
			100 kHz to 300 kHz	4.00 + 0.50	4.00 + 0.50	4.00 + 0.50	0.200 + 0.020
	1.000000 V to 750.000 V	1 μV to 1 mV	3 Hz to 5 Hz	1.00 + 0.02	1.00 + 0.03	1.00 + 0.03	0.100 + 0.004
			5 Hz to 10 Hz	0.35 + 0.02	0.35 + 0.03	0.35 + 0.03	0.035 + 0.004
			10 Hz to 20 kHz	0.04 + 0.02	0.05 + 0.03	0.06 + 0.03	0.005 + 0.003
			20 kHz to 50 kHz	0.10 + 0.04	0.11 + 0.05	0.12 + 0.05	0.011 + 0.005
			50 kHz to 100 kHz	0.55 + 0.08	0.60 + 0.08	0.60 + 0.08	0.060 + 0.008
			100 kHz to 300 kHz	4.00 + 0.50	4.00 + 0.50	4.00 + 0.50	0.200 + 0.020
True RMS 交流電流 (6)(7)(9)(10)	100.0000 μA (Burden Voltage < 0.011 V)	100 pA	3 Hz to 5 Hz	1.00 + 0.04	1.00 + 0.04	1.00 + 0.04	0.100 + 0.006
			5 Hz to 10 Hz	0.35 + 0.04	0.35 + 0.04	0.35 + 0.04	0.035 + 0.006
	10.00000 mA (Burden Voltage < 0.04 V)	10 nA	10 Hz to 5 kHz	0.10 + 0.04	0.10 + 0.04	0.10 + 0.04	0.015 + 0.006
			5 kHz to 10 kHz	0.18 + 0.04	0.18 + 0.04	0.18 + 0.04	0.030 + 0.006
	1.000000 mA (Burden Voltage < 0.11 V)	1 nA	3 Hz to 5 Hz	1.00 + 0.04	1.00 + 0.04	1.00 + 0.04	0.100 + 0.006
			5 Hz to 10 Hz	0.30 + 0.04	0.30 + 0.04	0.30 + 0.04	0.035 + 0.006
	100.0000 mA (Burden Voltage < 0.4 V)	100 nA	10 Hz to 5 kHz	0.10 + 0.04	0.10 + 0.04	0.10 + 0.04	0.015 + 0.006
			5 kHz to 10 kHz	0.15 + 0.04	0.15 + 0.04	0.15 + 0.04	0.030 + 0.006
	1.000000 A (Burden Voltage < 0.7 V)	1 μA	3 Hz to 5 Hz	1.00 + 0.04	1.00 + 0.04	1.00 + 0.04	0.100 + 0.006
			5 Hz to 10 Hz	0.30 + 0.04	0.30 + 0.04	0.30 + 0.04	0.035 + 0.006
			10 Hz to 5 kHz	0.10 + 0.04	0.10 + 0.04	0.10 + 0.04	0.015 + 0.006
			5 kHz to 10 kHz	0.15 + 0.04	0.15 + 0.04	0.15 + 0.04	0.030 + 0.006
	3.000000 A (Burden Voltage < 0.2 V)	1 μA	3 Hz to 5 Hz	1.00 + 0.04	1.00 + 0.04	1.00 + 0.04	0.100 + 0.006
			5 Hz to 10 Hz	0.35 + 0.04	0.35 + 0.04	0.35 + 0.04	0.035 + 0.006
			10 Hz to 5 kHz	0.23 + 0.04	0.23 + 0.04	0.23 + 0.04	0.015 + 0.006
			5 kHz to 10 kHz	0.23 + 0.04	0.23 + 0.04	0.23 + 0.04	0.030 + 0.006
	10.00000 A (Burden Voltage < 0.5 V)	10 μA	3 Hz to 5 Hz	1.10 + 0.04	1.10 + 0.04	1.10 + 0.04	0.100 + 0.006
			5 Hz to 10 Hz	0.35 + 0.04	0.35 + 0.04	0.35 + 0.04	0.035 + 0.006
			10 Hz to 5 kHz	0.15 + 0.04	0.15 + 0.04	0.15 + 0.04	0.015 + 0.006
			5 kHz to 10 kHz	0.35 + 0.04	0.35 + 0.04	0.35 + 0.04	0.030 + 0.006
頻率和週期特性		Accuracy : ± (% of reading)					
頻率 / 週期 (11)(12)(13)(14)	100.0000 mV to 750.000 V	—	3 Hz to 5 Hz	0.100	0.100	0.100	0.100
			5 Hz to 10 Hz	0.050	0.050	0.050	0.035
			10 Hz to 40 Hz	0.030	0.030	0.030	0.015
			40 Hz to 1 MHz	0.006	0.006	0.006	0.015

溫度特性							
溫度 (RTD) (15)	-200 °C to -100 °C	0.001 °C	—	—	—	0.09 °C	0.004 °C / °C
	-100 °C to -20 °C	0.001 °C	—	—	—	0.08 °C	0.005 °C / °C
	-20 °C to 20 °C	0.001 °C	—	—	—	0.06 °C	0.005 °C / °C
	20 °C to 100 °C	0.001 °C	—	—	—	0.08 °C	0.005 °C / °C
	100 °C to 300 °C	0.001 °C	—	—	—	0.12 °C	0.007 °C / °C
	300 °C to 600 °C	0.001 °C	—	—	—	0.22 °C	0.009 °C / °C
溫度 (熱電偶) (15)	-200 °C to +1000 °C	0.002 °C	E	—	—	0.2 °C	0.03 °C / °C
	-210 °C to +1200 °C	0.002 °C	J	—	—	0.2 °C	0.03 °C / °C
	-200 °C to +400 °C	0.002 °C	T	—	—	0.3 °C	0.04 °C / °C
	-200 °C to +1372 °C	0.002 °C	K	—	—	0.3 °C	0.04 °C / °C
	-200 °C to +1300 °C	0.003 °C	N	—	—	0.4 °C	0.05 °C / °C
	-50 °C to +1768 °C	0.01 °C	R	—	—	1 °C	0.14 °C / °C
	-50 °C to +1768 °C	0.01 °C	S	—	—	1 °C	0.14 °C / °C
+350 °C to +1820 °C	0.01 °C	B	—	—	1 °C	0.14 °C / °C	
溫度 (熱敏電阻) (15)	-80 °C to 150 °C	0.01 °C	—	—	—	0.01 °C	0.003 °C / °C
電容特性 <span style="float: right;">Accuracy : ± (% of reading + % of range)</span>							
電容 (16)	1.000 nF	—	2.00 + 2.00	2.00 + 2.00	2.00 + 2.00	0.05 + 0.01	2.00 + 2.00
	10.00 nF	—	2.00 + 1.00	2.00 + 1.00	2.00 + 1.00	0.05 + 0.01	2.00 + 1.00
	100.0 nF	—	2.00 + 0.40	2.00 + 0.40	2.00 + 0.40	0.05 + 0.01	2.00 + 0.40
	1.000 μF	—	2.00 + 0.40	2.00 + 0.40	2.00 + 0.40	0.05 + 0.01	2.00 + 0.40
	10.00 μF	—	2.00 + 0.40	2.00 + 0.40	2.00 + 0.40	0.05 + 0.01	2.00 + 0.40
	100.0 μF	—	2.00 + 0.40	2.00 + 0.40	2.00 + 0.40	0.05 + 0.01	2.00 + 0.40
顯示幕	4.3" color TFT WQVGA (480x272) with LED backlight						
介面	RS -232C, USB host/device, LAN, Digital I/O; GPIB(optional)						
使用電源	AC 100 V / 120 V / 220 V / 240 V ±10%						
電源頻率	50 Hz / 60 Hz and 400 Hz ±10%						
消耗功率	Max. 25 VA						
尺寸 (W x H x D)	267 mm x 107 mm x 302 mm ~ with bumper 220 mm x 88 mm x 277 mm ~ without bumper						
重量	Approx. 3.53 kg without option						

- [1]. DC Specification: In addition to the availability that requires warm-up of 60 minutes, it must be set in 5/s speed rate (60/s speed rate for Continuity and Diode), A-Zero on.
- [2]. The entire range of measurement will pass the set range by 20% except the tests of 1000 DCV, 750 ACV, 3 A DC, 3 A AC, 10 A DC, 10 A AC and diode.
- [3]. This specification applies to 4-wire resistance measurement, whilst it requires using "REL" function for offset on 2-wire resistance measurement. 2-wire resistance measurement will cause additional error of 0.2  $\Omega$  if REL function is not executed.
- [4]. This specification applies to the voltage measured from input terminal. 1 mA test current is the typical value. The change of current source leads to the variation in buck of diode junction.
- [5]. Accuracy is  $\pm$  (DC Input accuracy + DC Reference accuracy), where Input accuracy = DC Voltage accuracy for the Input HI to LO (in % of the Input voltage), and Reference accuracy = DC Voltage accuracy for the HI to LO (Sense) Reference (in % of the Reference voltage).
- [6]. The 10 A range of measurement is available for the terminals on front panel only. Due to power factor resulting in temperature rise, 2 mA increment per one ampere when input is greater than 5 Arms.
- [7]. AC Specification: It will be available after 60 minutes of warm-up, sine wave as well as 1/s speed rate.
- [8]. Specifications are for sinewave input > 5% of range. For inputs from 1% to 5% of range and < 50 kHz, add 0.1% of range additional error. For 50 kHz to 100 kHz, add 0.13% of range. The measurement range of 750 ACV is limited within the range of  $7.5 \times 10^7$  Volt-Hz.
- [9]. Three speed settings provided for low-frequency performance: 1/s (3 Hz), 5/s (20 Hz), 20/s (200 Hz). Additional errors will Not occur for the frequency greater than the filter settings.
- [10]. Specifications are for sinewave input >5% of range, and is beyond 10  $\mu$ A AC. For inputs from 1% to 5% of range, add 0.1% of range additional error.
- [11]. This specification will be available after 60 minutes of warm-up and sine wave input, unless stated otherwise. This specification applies to 1s gate time.
- [12]. This specification is available when both sine wave and square wave input  $\geq$  100 mV. For the input of 10 mV to 100 mV, the % of reading error needs to be multiplied by 10 times.
- [13]. The amplitude range is from 10% to 120% and is lower than 750 ACV.
- [14]. The input  $\geq$  60 mV, for 300 kHz to 1 MHz, within 100 mV range.
- [15]. The actual measurement range and test lead error will be constrained by the adopted test lead. The test lead accuracy adder covers all errors of measurements and ITS-90 temperature change.
- [16]. Specifications are for film Capacitance inputs that are greater than 10% range

**固緯電子實業股份有限公司**

新北市土城區中興路7-1號  
T (02)2268-0389 F (02)2268-0639  
E-mail: [marketing@goodwill.com.tw](mailto:marketing@goodwill.com.tw)

台中 台中市五廊街124號9樓之2  
T (04) 2372-2809 F (04) 2372-5802

高雄 高雄市前鎮區新街路286之4號7樓之1  
T (07) 831-7317 F (07) 831-7327

**固緯電子(蘇州)有限公司**

江蘇省蘇州市新區珠江路521號  
T 0512-6661-7177 F 0512-6661-7277  
E-mail: [marketing@instek.com.cn](mailto:marketing@instek.com.cn)

上海 上海市宜山路 889 號 2 號樓 8 樓  
T 021-6485-3399 F 021-5450-0789

深圳 深圳市寶安西鄉街道共樂路西香商會大廈1105  
T 0755-2919-0632 F 0755-2907-6570

**GW INSTEK**

Simply Reliable

[www.gwinstek.com](http://www.gwinstek.com)[www.facebook.com/GWInstek](https://www.facebook.com/GWInstek)